



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF3240-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1150 @ 0°C	480	5 ± 1	28,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION			
	DRAWN BY L. WENGSTROM	APP'VD BY DATE FD 8/2/01	SIZE A	FSCM NO. 55335	DRAWING NO. BF3240-24B
TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP					
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 8/1/01	REVISION DATE	REV. NO.
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	RELEASED DATE	REVISION DATE	SHEET 1 OF 1

RELEASE AND CANCEL P-0105-05	8/1/01
REV. NO.	DESCRIPTION/ECO NUMBER
APP'VD DATE	