

Safe-IT 6-Outlet Surge Protector, Retractable USB Charger, 5-15R Outlets, 4 USB Charging Ports, 8 ft. (2.4 m) Cord, Antimicrobial Protection

MODEL NUMBER: TLP68UBAM











Safely charges and powers up to 10 devices, including laptops and tablets, during important work-fromanywhere meetings and conferences.

Features

6-Outlet Surge Protector Safeguards Your Sensitive Electronics

Ideal for your home or office workstation or travel use, this Safe-ITTM surge protector features a surge protection rating of 1080 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP68UBAM protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp or other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Two outlets are spaced apart to accept bulky transformers or large plugs without blocking adjacent outlets.

Retractable USB Charger Offers Easy Access to Mobile Devices

The USB charger with retractable 4.5-foot (1.4-meter) cord clamps to the edge of your desk or work surface for convenient access to four USB-A ports, while the AC outlets remain out of your way. The USB ports share 3.4A for charging your smartphone, tablet and other USB mobile devices.

Filtering EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive electromagnetic and radio frequency interference that can inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Work Environment. The Safe-IT TI P68UBAM features antimicrobial protection that helps resist the growth of bacteri

The Safe-IT TLP68UBAM features antimicrobial protection that helps resist the growth of bacteria, viruses, fungi, mold and mildew.

Premium Safety Features Protect Your Valuable Equipment

The on/off switch provides one-touch control over connected equipment. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. A green LED confirms your connected equipment is protected.

Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1080 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 3.4A for fast charging of phones, tablets and other mobile devices
- Retractable USB charger clamps to your desk to keep mobile devices within easy reach
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

Package Includes

- TLP68UBAM 6-Outlet Surge Protector with Retractable USB Charger
- · Owner's manual



Specifications

OVERVIEW UPC Code 037332255814 Product Type Surpe Protector Charging Form Factor Strip Device Compatibility Phone; Tablet; Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Pug Features Right Angle (38D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Pug Type NEMA 5-15P Input Cord Length (t) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Curcuit Ereaker (amps) 15 Transformer Accommodation (4) Yes Sight-Angle Outlets Yes USER INTERFACE, ALERTS & COM-Libration AC circuit breaker and 2 position on/oif power switch Diagnostic LED Details Built in LED confirms suppressor "protection present" (green)			
Product Type Surge Protector Charging Form Factor Strip Device Compatibility Phone; Tablet; Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120 V AC Recommended Electrical Service 120 V (110-125V) Input Plug Features Right Angle (36D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Suit-in LED confirms suppressor "protection present" (green) status	OVERVIEW		
Charging Form Factor Strip Device Compatibility Phone: Tablet. Amazon Kindle INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Plug Features Right Angle (36D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTINUED Suppressor 'protection present' (green) status Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor 'protection present' (green) status </th <th>UPC Code</th> <th>037332265814</th>	UPC Code	037332265814	
Device Compatibility	Product Type	Surge Protector	
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Plug Features Right Angle (38D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility No Coutput Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED (s) Self-Angle Circuit breaker and 2 position on/off power switch Diagnostic LED Details Bull-in LED confirms suppressor "protection present" (green) status CHARGING Transformer Accommodation Bull-in LED confirms suppressor "protection present" (green) status CHARGING	Charging Form Factor	Strip	
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 120V (110-125V) Input Plug Features Right Angle (36D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Circuit Breaker (amps) 15 Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Device Compatibility	Phone; Tablet; Amazon Kindle	
Recommended Electrical Service 120V (110-125V) Input Plug Features Right Angle (36D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & COWNOLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	INPUT		
Input Plug Features Right Angle (36D) Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & COMBINATION Surpressor "protection present" (green) status CHARGING	Nominal Input Voltage(s) Supported	120V AC	
Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Circuit Breaker (amps) 15 Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Recommended Electrical Service	120V (110-125V)	
Voltage Compatibility (VAC) Maximum Surge Amps 36000 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED (S) Versum Surge Amps 36000 NEMA 5-15P NEMA 5-15P NeMA 5-15P No No No No No No No No No N	Input Plug Features	Right Angle (36D)	
Maximum Surge Amps Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Input Cord Gauge Type	14 gauge; SJT	
Input Plug Type NEMA 5-15P Input Cord Length (ft.) 8 Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED (s) Built-in LED confirms suppressor "protection present" (green) status CHARGING	Voltage Compatibility (VAC)	120	
Input Cord Length (ft.) Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Maximum Surge Amps	36000	
Right-Angle Plug No Input Cord Length (m) 2.44 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Input Plug Type	NEMA 5-15P	
Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Input Cord Length (ft.)	8	
Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status CHARGING	Right-Angle Plug	No	
Output Prequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Input Cord Length (m)	2.44	
Frequency Compatibility 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Integrated Cord Clip	No	
Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	OUTPUT		
Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Frequency Compatibility	60 Hz	
Transformer Accommodation (4) Yes Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Output Receptacles	(6) 5-15R	
Right-Angle Outlets Ves USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status CHARGING	Circuit Breaker (amps)	15	
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status	Transformer Accommodation	(4) Yes	
Diagnostic LED(s) Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status CHARGING	Right-Angle Outlets	Yes	
Switches Combination AC circuit breaker and 2 position on/off power switch Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status CHARGING	USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED Details Built-in LED confirms suppressor "protection present" (green) status CHARGING	Diagnostic LED(s)	Yes	
CHARGING	Switches	Combination AC circuit breaker and 2 position on/off power switch	
	Diagnostic LED Details	Built-in LED confirms suppressor "protection present" (green) status	
Number of Charging Ports 4	CHARGING		
	Number of Charging Ports	4	



Total Charging Amps	3.4A	
Total Charging Watts	17	
Charging Method	USB	
Charging Port Type	(4) USB A (FEMALE)	
Charging Ports / Amps	(4) 3.4A	
Overcharge Protection	No	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1080	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
UL1449 Let Through Rating	400V	
EMI / RFI Filtering	Yes	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Power Cord Color	Black	
Housing Color	Black	
Mounting Holes or Slots	No	
Receptacle Color	Black	
Shipping Weight (lbs.)	1.63	
Shipping Weight (kg)	0.74	
Unit Dimensions (hwd / in.)	8.300 x 3.600 x 1.400	
Unit Dimensions (hwd / cm)	24 x 17 x 4.6	
Unit Weight (lbs.)	1.8	
Unit Weight (kg)	0.82	
FEATURES & SPECIFICATIONS		
Antimicrobial	Yes	
Antimicrobial Rotatable Outlets	Yes No	



STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1449; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$50,000 Ultimate Lifetime Insurance	



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.