



Technical Datasheet

1 Mil High Temperature Masking Tape RoHS & REACH Compliant PPT Series

High Temperature Masking Tapes are made of 1 mil thick polyimide film with 1.5 mil thick silicone adhesive. These tapes are reliable and durable with a unique combination of electrical, thermal, chemical, and mechanical properties that withstand extreme temperatures, vibration, and other demanding environments. High Temperature Masking Tapes are packaged on a 3" core and are 36 yards long.

APPLICATIONS: 3D Printing, Aerospace Assembly, Auto Manufacturing, Electronic Assembly, Fiber Optics Manufacturing, and Solar Panels.

TYPICAL PHYSICAL PROPERTIES ⁽¹⁾

Color	Amber
Adhesion Type	Silicone
Film Thickness	1 Mil
Adhesive Thickness	1.5 Mil
Total Thickness	2.5 Mil
Tensile Strength	30 lbs./inch
Elongation	55 %
Operating Temperature	-73°C (-100°F) - 260°C (446°F)
Dielectric Strength	6,500 Volts
Resistance to acids, oils, solvents	Excellent
Length	36 Yards

⁽¹⁾ Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.

Bertech makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.