



Features

- Optional non-Liquid-cooled 500A charging connector*
- Simultaneous 2 DC Charging
- Multi-standard: CCS, CHAdeMO and GB/T
- Network or standalone operation
- User authentication
- Optional cable management accessories
- Supports smart charging and load balancing
- Efficiency > 94%; PF > 0.99 (APFC)
- 7-inch LCD screen with user friendly interface
- OCPP 1.6 JSON
- IK10/NEMA 3R(Not including screen and RFID module), IP55
- Customization available
- Eichrect compliant: Q3/2021 LEM mater, Eichrecht certification TBD starting Q4/2021

Applications

- Parking Garage
- Commercial fleet
- EV infrastructure operators and service

| FSP SERIES

120kW DC Fast Charger




Scan to order and see additional product features and services.

©2021 TurnOnGreen, Inc. .

For pricing & information:

sales@turnongreen.com 1-877-634-0982

Model Name	FSP1200	
Safety	NRTL - cETLus	
Picture		
Power Specification		
AC Input	Input Rating	3 Φ 480Vac (+10%,-15%)
	AC Input Connection	3P+N+PE (Wye configuration), TN/TT
	Max. Input Current	DC System:3 Φ 170A
	Frequency	50Hz/60Hz
	Power Factor	>0.99
	Efficiency	>94%, at optimize VI/point
DC Output	Output Voltage Range	<ul style="list-style-type: none"> CCS1: 150~950Vdc CHAdeMO: 150~500Vdc
	Max. Output Current	<ul style="list-style-type: none"> CHAdeMO 120A@500V CCS1:200A@600V, optional 300A
	Max. Output Power	DC System: 120kW
	Voltage Accuracy	\pm 2%
	Current Accuracy	\pm 2%
User Interface & Control		
Display	7" TFT-LCD	
Push Buttons	Operation button/Emergency stop button	
User Authentication	RFID: support ISO 14443A/B, ISO 15693, FeLiCa Lite-S (RCS966) OCPP, 2D barcode, APP, Mobile Payment	
Communication		
External	Ethernet, Wi-Fi, and 4G	
Internal	CAN bus/RS485	
Environmental		
Operating Temperature	-30°C~50°C, will derating from 50°C and above	
Humidity	5%~95% RH, non-condensing	
Altitude	\leq 2000M	
IP/IK Level	<ul style="list-style-type: none"> NEMA 3R/IK10 (not including screen and RFID module) 	
Cooling Method	Fan cooling	
Mechanical		
Cabinet Dimension(W x D x H)	800 x 650 x 1900mm \pm 1%	
Weight	\leq 420kg \pm 1%	
Cable Length	4m	
Protection		
Input Protection	OVP, OCP, OPP, OTP, UVP, SPD	
Output Protection	OCP, SCP, OVP, LVP, OTP, IMD	
Regulation		
Certificate	UL 2202, UL2231	
Charging Interface	CHAdeMO V1.2, DIN 70121, ISO15118, GB/T 27930	