

Russellstoll[®]

FS/FD Metallic Connections Systems

T&B Catalog Number:



UPC Number: 3760
70891714998
Status: Active
Description:

FS/FD Metallic Connection- 20-30 Amp, 600VAC-250VAC, Aluminum Male Plug, 3 Pole 4 Wire

Features

Precision-made, self-aligning and self-wiping contacts; receptacles provided with spring-actuated, self-closing flaps; available in watertight and weathertight versions; solderless screw terminals for convenient wiring

Mechanical linkage prevents plug insertion or withdrawal unless switch is in "off" position; Circuit breaker protection available on many models; Ground contacts are "make first," "break last"



Application

Designed for lower-ampereage marine and rough service applications with rugged die cast aluminum housings and epoxy powder coated finishes.

Designed for lower-ampereage marine and rough service applications with rugged die cast aluminum housings and epoxy powder coated finishes.

General

Style	Male Plug
Material	Contact carrier interior is Thermoset; Cast aluminum or brass for housing, gland nuts, screw collar rings
Material_1	Brass pins and sleeves; Brass or aluminum gland friction washer
Material_2	Hinge Pins (receptacles), Terminal screws, Flap Springs, Assembly Screws, Nuts, and Hardware are stainless steel; Terminals are brass
Frequency	60 Hz
Amperage	30 Amp
Pole/Wire	3P/4W
System	Washdown Industrial & Light Marine

Specifications

Voltage 600 Volts AC

Packaging

T&B Inner Pack	1
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	0.6 lbs. Each

Application Support

Overview	Available on Website
Russellstoll Application Guide	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com