



Note:

1. Material:

- 1.1 Housing: High temperature thermoplastic UL94v-0
- 1.2 Contact: copper alloy, t=0.20mm
- 1.3 Shell: Stainless steel, t=0.20mm
- 1.4 Latch: Stainless steel, t=0.35mm

2. Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 50 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 35N Max.
- 2.6 Total unmating force: 10N Min.
- 2.7 DURABILITY: 10000 CYCLES
- 2.8 Temperature range: -30° C~80° C
- 3. SALT SPRAY : 24H AT 35%DC WITH 5%-SALT-SOLUTION CONCENTRATION.
- 4. 符合 UL 94 3.2mm V0防火等级.

1	2	3	4	5	6	7	8
A	B	C	D	E	F	A	B

ITEM	MODIFICATION	DATE	DRAW	APPROVE
△	新发行	2013-07-06	袁腾武	

PRD.J		深圳市精拓金电子有限公司	
DIMENSION STYLE	MM ONLY		
DESIGN UNIT	METRIC	Z	Y B
SCALE	1:1	郭	治 富

TOLERANCE UNLESS OTHERWISE SPECIFIED	
X:±0.35	X:±5°
X:X±0.25	X:X±3°
X:XX±0.15	X:XX±2°

TITLE	MICRO USB 2.0单排焊线	SHEET NO.	1 OF 1
PART NO.	SEE TABLE	REV.	A0
MOLD NO.	XPTMBM-A00014		