



RECOMMENDED PCB LAYOUT

MAPX	MODIFICATION	DATE
------	--------------	------

- NOTES:
1. MATERIALS
 - INSULATOR: LCP 30%GF ,UL94V-0
 - SHELL: SUS WITH NI PLATED.
 - CONTACT: BRASS WITH AU 1U" PLATED ON CONTACT AREA, AND SN 100U" PLATED ON SOLDER TAIL.
 - INSERT FORCE: 35N MAX.
 - PULLING FORCE: 8N MIN,
 - DURABILITY: 10000 CYCLES.
 2. ELECTRICAL
 - INSULATION RESISTANCE: 500 MEGOHMS MINIMUM.
 - DIELECTRIC WITHSTANDING VOLTAGE: 250V DC R.M.S.
 - VOLTAGE RATING: 150V.
 - CURRENT RATING: 0.5 AMP.
 - CONTACT RESISTANCE: 15 MILLIOHMS MAXIMUM.
 3. ENVIRONMENTAL
 - TEMPERATURE RANGE: -55°C TO +105°C.

产品图

深圳市精拓金电子有限公司

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE	公差
X	±0.25
X	±5°
X	±0.20
X	±2°
XX	±0.15
XX	±1°
XXX	±0.10
XXX	±0.5°

单位	制图	制图料号	产品名称	角法	版本
UNITS	DRAWING	PRODUCT PART NO	PRODUCT NO	VIEW	VER
MM	审核	Z-Y-B	MICRO SP MALE SMT type		
比例	核准		(前五后五)		
1:1	APPD				AD
日期	DATE	20120911			

1 2 3 4 7 8 9 10