

PRODUCT SELECTOR

PRODUCT TYPE	POSITIONS	IP RATING	AMPERAGE	HOUSING MATERIAL	PRODUCT LINE
Search All ▼	Search All ▼	Search All ▼	Search All ▼	Search All ▼	Search All ▼

VOLTAGE

Search All ▼	RESET	SEARCH
------------------------------	-------	--------

Home > Our Product Lines > C091 Connectors > C091 B > 4 Position Receptacles > T 3327 150 - M16 Rear mounting straight Female metal receptacle with ring nut. 4 contacts. Contacts sold separately.



T 3327 150 - M16 REAR MOUNTING STRAIGHT FEMALE METAL RECEPTACLE WITH RING NUT. 4 CONTACTS. CONTACTS SOLD SEPARATELY.

PART NUMBER: T3327150

SPECIFICATIONS:

Contacts: 4
Current Rating: 10A
Termination: Crimp
Locking: Bayonet; outside lock
Insert: Thermoplastic
Version: Straight; metal
Wire Gauge: 0.09 - 1.0mm² (28-18 AWG)
Housing: Zinc die cast, nickel plated
Protection: IP40
Insertion/Withdrawal Force: 30 N
Insulation Resistance: > 10(10) Ω
Rated Voltage IEC 60664-1: 300V
Rated Voltage per UL 1977: 250V
Rated Impulse Withstanding Voltage IEC 60664-1: 1500V
Contact Resistance: < 5 m ohms
Mount: Rear w/ring nut
Operating Temperature: -40°C to +100°C
Mating Part(s): T3324551, T3324552, T3324554, T3324055
Size: M16

QUANTITY

[REQUEST A QUOTE](#)

Like Sign Up to see what your friends like.

Like Sign Up to see what your friends like.

Rear mounting straight female metal receptacle with ring nut (hex nut available upon request). 4 contacts. Bayonet locking outside (mateable with locking inside). Contacts sold separately.

RELATED ITEMS



T 3324 551 - M16 Male straight cable connector with internal strain relief and plastic locking ring. 4 contacts, 4-6mm cable diameter. Contacts sold separately.



T 3324 552 - M16 Male straight cable connector with internal strain relief and plastic locking ring. 4 contacts, 6-8mm cable diameter. Contacts sold separately.



T 3324 554 - M16 Male straight cable connector with internal strain relief and plastic locking ring. 4 contacts, 4-6mm cable diameter. Contacts sold separately.



T 3324 055 - M16 Male right angled cable connector with internal strain relief and plastic locking ring. 4 contacts, 4-6mm cable diameter. Contacts sold separately.



T 3328 551 - M16 Female straight cable connector with black cable sleeve. 4 contacts, 4-6mm cable diameter. Contacts sold separately.



T 3328 552 - M16 Female straight cable connector with internal strain relief and clamping ring. 4 contacts, 6-8mm cable diameter. Contacts sold separately.



T 3328 554 - M16 Fe Male Cable Connector with Internal Strain relief and Plastic Locking Ring. Contacts sold separately.



T 3327 550 - M16 Straight, full plastic front mounting female receptacle with snap-in mount. 4 contacts. Contacts sold separately.

BROWSE SIMILAR ITEMS

- > Market Applications > Heavy Equipment > Agriculture > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Heavy Equipment > Construction > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Heavy Equipment > Transportation > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Heavy Equipment > Off Road Recreation > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Heavy Equipment > Industrial > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Automation > Conveyors > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Automation > Packaging Machinery > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Automation > Motion Control / Servo Motors > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Medical > C091 Connectors > C091 B > 4 Position Receptacles
- > Market Applications > Wireless Infrastructure > C091 Connectors > C091 B > 4 Position Receptacles

LINKS

- > [Company](#)
- > [Contact](#)
- > [Privacy Policy](#)
- > [Terms and Conditions](#)
- > [Code of Business Conduct and Ethics](#)
- > [ISO Certification](#)
- > [Quality Policy](#)
- > [Industrial@Amphenol News](#)
- > [Test Reports](#)

SHOP

- > [Our Product Lines](#)
- > [Market Applications](#)
- > [Distributors](#)

FOLLOW US!

