

PRODUCT SELECTOR

PRODUCT TYPE	POSITIONS	IP RATING	AMPERAGE	HOUSING MATERIAL	PRODUCT LINE
Search All ▼	Search All ▼	Search All ▼	Search All ▼	Search All ▼	Search All ▼

VOLTAGE

[Search All](#) ▼ [RESET](#) [SEARCH](#)

Home > Our Product Lines > C091 Connectors > C091 D+ > 6 Position Cable Connectors > C091 11H006 001 4 - M16 Male cable connector with internal strain relief and metal locking ring. 6 contacts, 6-8mm cable diameter.



C091 11H006 001 4 - M16 MALE CABLE CONNECTOR WITH INTERNAL STRAIN RELIEF AND METAL LOCKING RING. 6 CONTACTS, 6-8MM CABLE DIAMETER.

PART NUMBER: C09111H0060014

[DATASHEET](#): [View / Download](#)

SPECIFICATIONS:

Contacts: 6
Cable Diameter: 6 - 8mm
Current Rating: 7A
Termination: Crimp
Locking: Screw
Insert: Thermoplastic
Version: Straight; metal
Wire Gauge: 0.09 - 1.0mm² (28-18 AWG)
Housing: Zinc die cast, nickel plated
Protection: IP 69K / IP 68
Insertion/Withdrawal Force: 50 N
Insulation Resistance: > 10(10) Ω
Rated Voltage IEC 60664-1: 300V
Rated Voltage per UL 1977: 250V
Rated Impulse Withstanding Voltage IEC 60664-1: 1500V
Contact Resistance: < 5m ohms
Sealing Material: Chloroprene
Operating Temperature: -40°C to +100°C
Mating Part(s): C09111D0060014,C09111N0060002,C09111G0060002
Size: M16

QUANTITY

[REQUEST A QUOTE](#)


Sign Up to see what your friends like.



Sign Up to see what your friends like.

DESCRIPTION

Male cable connector with internal strain relief and metal locking ring. 6 contacts, 6-8mm cable diameter. Complete EMI shielding in the fully mated and locked position (EMI security). Screw locking according to IEC 61076-2-106. Fully intermateable with C091D connectors. Contacts sold separately.

RELATED ITEMS



C091 11H006 001 2 - M16 Male cable connector with internal strain relief and metal locking ring. 6 contacts, 6-8mm cable diameter. Contacts sold separately.



C091 11N006 000 2 - M16 Front mounting female metal receptacle with O-ring seal and ring nut mount. 6 contacts. Contacts sold separately.



C09111G0060002 Rear mounting female metal receptacle with O-ring seal and ring nut mount. 6 contacts.



C091 11D006 001 4 - M16 Female cable connector with internal strain relief and metal locking ring. 6 contacts, 6-8mm cable diameter.

BROWSE SIMILAR ITEMS

- > Market Applications > Heavy Equipment > Agriculture > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Heavy Equipment > Construction > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Heavy Equipment > Transportation > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Heavy Equipment > Off Road Recreation > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Heavy Equipment > Industrial > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Automation > Conveyors > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Automation > Packaging Machinery > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Automation > Motion Control / Servo Motors > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Medical > C091 Connectors > C091 D+ > 6 Position Cable Connectors
- > Market Applications > Wireless Infrastructure > C091 Connectors > C091 D+ > 6 Position Cable Connectors

LINKS

- > Company
- > Contact
- > Privacy Policy
- > Terms and Conditions
- > Code of Business Conduct and Ethics
- > ISO Certification
- > Quality Policy
- > Industrial@Amphenol News
- > Test Reports

SHOP

- > Our Product Lines
- > Market Applications
- > Distributors

FOLLOW US!



