

Pin bars 5,0 mm for PCBs



ST 15... straight, laterally closed



- Pin-bars with soldering pins
- 2...12 poles
- Laterally open or closed
- Straight or bent design
- Activating at only zero-voltage

Nominal voltage UL 300 V, VDE 250 V
 Nominal current UL 15 A, VDE 12 A
 Insulation material PA, UL94 V-0, green RAL 6018
 Temperature range -30...+105 °C



Type laterally closed

Type ST 17

Type ST 16

Type laterally closed

Art.No	Type	Poles	RoHS	Price per 1 in EUR			Stock	Quantity	
				1+	10+	50+			
142266	ST 1502	2	▲	0.21	0.20	0.18	✓✓	<input type="text" value="1"/>	
142267	ST 1503	3	▲	0.32	0.30	0.27	✓✓	<input type="text" value="1"/>	
142268	ST 1504	4	▲	0.43	0.40	0.36	✓✓	<input type="text" value="1"/>	
142269	ST 1505	5	▲	0.53	0.49	0.46	✓✓	<input type="text" value="1"/>	
142270	ST 1506	6	▼	0.64	0.59	0.55	✓✓	<input type="text" value="1"/>	
142271	ST 1508	8	▼	0.85	0.79	0.73	✓✓	<input type="text" value="1"/>	
142272	ST 1510	10	▲	1.07	0.99	0.91	✓✓	<input type="text" value="1"/>	
142273	ST 1512	12	▲	1.28	1.19	1.09	✓✓	<input type="text" value="1"/>	

▲ = RoHS comp. ▼ = RoHS not comp. ✓✓ = available ex-stock ✓ = will be ordered for you = put in shopping cart = incl. in list
 Prices in EUR excl. VAT