


#### **BNC Female Breakout Style to Stackable Single Banana Plugs**

- Tarnish resistant, plated brass body; gold-plated brass center contact.
- ABS housing.
- Nine–leaf beryllium copper spring and copper alloy 360 bodies
- Hook-up wire: #20 AWG ( 41/36) tinned copper with 105°C PVC insulation.
- Product Data Sheet
- Send us your questions about this product






# BU-5231-A-4-0

- BNC Female Breakout Style To Insulated Mini–Alligator Clips
- Tarnish resistant, plated brass with gold–plated brass center contact.
- ABS housing.
- Clips: No. 30BL with No. 31 insulators.
- Tip jack: accepts 0.080" (2.0 mm) dia. pin.
- Hook–up wire: #20 AWG (41/36) tinned copper with 105° PVC insulation.
- Product Data Sheet
- Send us your questions about this product

# BU-5244-A-4-0

#### BNC Female Breakout to Stackable 0.080" (2.0mm) Pin Plugs

- Tarnish resistant, plated brass body; gold–plated brass center contact.
- ABS housing.
- Pin tip: Nickel-plated brass, 0.080" (2.0mm) dia., 0.500" (12.7 mm) long.
- Tip jack: accepts 0.080" (2.0mm) dia. pin; Body is nickel–plated alloy 360 copper.
- Hook–up wire: #20 AWG (41/36) tinned copper with 105° PVC insulation.
- Product Data Sheet
- Send us your questions about this product



## Contents Next

## Home|Insulated BNCs|Clips & Insulators|Insulated Test Accessories Accessories & Probes|Kits|Cross Reference

@1999-2000 Mueller Electric Company. All rights reserved. Problems with the site should be reported to the webmaster.